

TECHNICAL DATA SHEET

en

Name of product:

FAXE H2O Terraceoil 0586

Type of product:	Waterborne Woodcare Oil containing linseed oil, naturel oils and active ingredients.
Application:	Treatment and renovation of cleaned wooden terraces and wooden garden furniture. This product has been developed for exterior use.
Properties:	Protects from the elements and gives the wood a water-repellant surface. It also retains the woods natural appearance and color.
Solids:	28 weight % 28 vol. %
Pre-treatment:	Clean the wood with FAXE Decking Cleaner to remove all dirt and desopits.

Application:

Method:	Recommended viscosity:	Thinner:
Paint Brush	No thinning required	-

The product needs to be stirred well before and while it is used. If several buckets are going to be used, mix them together first.

Drying:

	Drying time	Film thickness - dry
Dry to touch	1 hour 20 °C	-

System Specification:

1. Cleaning with FAXE Decking Cleaner. Spray or apply the Cleaner with brushes or paint brushes on a dry surface. After one or two days the contaminants can be removed with a stiff brush or broom. Rinse with water and dry the surface.
2. Application of FAXE H2O Terraceoil.
3. Highly absorbent wood has to be treated several times.

Coverage:	Theoretical: 7 m ² /ltr.
Storage:	Frostfree, cool, and closed.
Shelf-life:	12 Months in an unopened container
Cleaning:	Tools clean with water.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk