

TECHNICAL DATA SHEET

en

Name of product:

Arsinol®, transparent 0170

Type of product: Wood preservative containing vegetable oils and active ingredients.

Application: Wood preservative for exterior use. Used for final treatment of exterior wood, for previously treated wood with transparent wood protection or to improve the adhesion, if the wood later on will be treated with covering wood protection products. This product has been developed for exterior use.

Properties: Arsinol 0170 provides protection and prevent the wood from drying out.

Solids: 33 weight % 28 vol. %

Pre-treatment: Clean the wood for dirt and loose paint with a stiff brush. The wood must be completely dry before painting. Coverings can be removed using FAXE Terrace Cleaner 0580 99300.

Application:

Method:

Paint Brush

Recommended viscosity:

No thinning required

Thinner:

The temperature must be between 5 and 25 °C and the relative humidity below 80%.

Keep surface coatings wet until completed, i.e. coat one or two boards in their full length to avoid unsightly overlapping.

Arsinol® transparent must be stirred before and during use.

Drying:

	Drying time	Film thickness - dry
Dry to touch	6-8 hours 20 °C	-
Dry to recoat	24 hours 20 °C	-

System Specification:

Priming: Arsinol Wood Impregnation, series 0169

Final Coat: Arsinol Transparent, series 0170

If an opaque coating is desired, you may finish with Arsinol series 0171 or Arsinol® EXTRA series 0175.

Coverage: Theoretical: 12 m²/ltr.

Storage: Dry and frost free.

Shelf-life: 24 Months in an unopened container

Cleaning: Tools clean with white spirit 79120.

Available colors: Please see our color card for information on the color range.

VOC explanation: Product marking: 2004/42/IIA(X)(YY)ZZZ

EU directive number: 2004/42/

Directive annex number: IIA

Product subcategory: (X)

VOC content limit value g/l 2010: (YY)

Maximum VOC Content in this product when ready for use, g/l: ZZZ

Please see the can label for information regarding VOC content.

Note:

Avoid applying in direct sunlight. Contains drying oil. Used rags may spontaneously ignite. Used rags should be stored in a fire-proof container or an airtight bag and discarded .

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk