

TECHNICAL DATA SHEET

en

Name of product:

FAXE Maintenance Oil 0245

Type of product: Oil based on refined vegetable oil and isoparaffin. The VOC of FAXE Maintenance Oil 0245 is lower than of FAXE Maintenance Oil 0277.

Application: Care and maintenance of wooden surfaces, which is treated with naturel curing oil eg. FAXE Wood Oil

Properties: Gives the wood a water and dirt repellent surface. It also retains its natural appearance and color.

Solids: 46 weight % 38 vol. %

Pre-treatment: Clean the wood to remove all grease and dirt. The wood should be dry before further treatment. FAXE Wood Cleaner, which effective removes residues of woodcare products, can be used.

Application:

Method:

Lint-free rags

Recommended viscosity:

No thinning required

Thinner:

Drying:

Dry to use

Drying time
4-8 hours 20 °C

Film thickness - dry
-

System Specification:

FAXE Maintenance Oil is applied with a lint-free cloth. The oil is polished into the floor with either a cloth or a polishing machine. Excess of oil is removed with dry cloths.

Coverage: Theoretical: 25 m²/ltr.

Storage: Store at minimumum. 5 ° C.

Shelf-life: 12 Months in an unopened container

Note: Dont use water on the treatment for the first 3 days.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk