

TECHNICAL DATA SHEET

en

Name of product:

FAXE Combicolor 0298

Type of product:	FAXE Combicolor is a mineral pigment based color concentrate.
Application:	All FAXE oils, lyes and panel lyes can be coloured to meet individual requirements using Faxe Combicolor.
Properties:	Color finishes to oak, beech, ash, pine, spruce and larch look particularly attractive.

Application:

Method:	Recommended viscosity:	Thinner:
---------	------------------------	----------

-

-

-

Pour approx. half of the 2.5 l of oil into a paint bucket. Shake 1 can of FAXE Combicolour vigorously and pour the complete contents into the paint bucket. Mix thoroughly using the mixing rod. Pour the remaining oil into the bucket, whilst stirring continuously.

The oil is now ready for use and can be applied in the same way as described for oil.

Usage: Mixing proportion - up to 10%

Storage:	Frostfree, cool, and closed.
Shelf-life:	24 Months in an unopened container
Cleaning:	Tools clean with white spirit.

Note: If several containers containing identical product are to be used, they should be mixed together first in order to ensure a uniform result. It is always recommended to make a small test area to check surface, adhesion and colour tone.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk