

TECHNICAL DATA SHEET

en

Name of product:

Faxe Hard Wax Oil

Type of product:	Floor oil based on refined vegetable oils and natural waxes.
Application:	Oil treatment of wooden floors. Can be used for all wood types.
Properties:	The oil penetrates into the wood, while the wax remains as care on the surface.
Solids:	60 weight % 52 vol. %
Pre-treatment:	The wood has to be sanded, clean and dry.

Application:

Method:	Recommended viscosity:	Thinner:
Industrial roller coater	50-60 sec. DIN-cup 4 mm	White spirit

Drying:

	Drying time	Film thickness - dry
Dry to use	4 hours 20 °C	9 - 12 g / m ²

System Specification:

- 1x sanding
- 1x Faxe Hard Wax Oil
- If necessary 1x sanding
- If necessary 1x Hard Wax Oil

Coverage:	Theoretical: 43 m ² /ltr.
Storage:	Frostfree, cool, and closed.
Shelf-life:	12 Months in an unopened container
Cleaning:	Application machines can be cleaned with Faxe Machinecleaner.
VOC explanation:	Product marking: 2004/42/IIA(X)(YY)ZZZ EU directive number: 2004/42/ Directive annex number: IIA Product subcategory: (X) VOC content limit value g/l 2010: (YY) Maximum VOC Content in this product when ready for use, g/l: ZZZ Please see the can label for information regarding VOC content.

Note:	Maintenance: The floor has to be sanded and washed with Faxe Intensive Cleaner. Thereafter Faxe Hard Wax Oil can be applied.
--------------	---

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk