

**TECHNICAL DATA SHEET****en**

Name of product:

**Efadur Catalyst 0455 - xxxxx**

**Type of product:** Prepolymer isocyanate catalyst for air-drying alkyd paints, e.g. Machine Enamel series 0130. Mixing: max. 10 - 15 % by volume.

**Application:** Catalyst for alkyd enamels.

**Properties:** Reduces drying time and improves gloss, toughness and chemical resistance.

**Solids:** 29 weight %      23 vol. %

**Storage:** Store cool and dry

**Shelf-life:** 12 Months in an unopened container

**Note:** Cellulose thinner destroys the effect of Efadur Catalyst. Therefore, use Synthetic Thinner 0700 - 68063 or other alcohol-free thinners. After Efadur Catalyst is mixed with alkyd paints the product should be used within 8 hours.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**Esbjerg Farve- & Lakfabrik A/S****Energivej 13****DK- 6700 Esbjerg****Ph. +45 75 12 86 00    FAX +45 75 45 33 68    e-mail: [info@esbjergpaints.dk](mailto:info@esbjergpaints.dk)****[www.esbjergpaints.dk](http://www.esbjergpaints.dk)**