

**TECHNICAL DATA SHEET****en**

Name of product:

**FAXE Decking Cleaner Conc. 0580 99300****Type of product:** Water-borne concentrated cleaning agent.**Application:** Depth cleaning of wooden decking and tiles. FAXE Decking Cleaner Conc. is suitable for cleaning of patio coverings made of untreated or oiled wood, stone or composite material.**Properties:** FAXE Decking Cleaner Conc. removes coatings and prevents their rapid new formation. When using a scrubber with stiff bristles the cleaning is very quickly and efficiently, also for profiled surfaces.**Application:**

<b>Method:</b>	<b>Recommended viscosity:</b>	<b>Thinner:</b>
Brush	-	water
Scrub	-	water

\* The terrace is wetted before treatment.

\* Scrub the surface with undiluted FAXE Decking Cleaner.

\* The following day rinse off loosened dirt and algae with plenty of water.

\* Leave the terrace to dry.

The finished result depends, amongst other things, on the preparatory treatment, structure and natural colour of the substrate. For this reason, try out first on a sample area.

**System Specification:**

After Care:

Finally FAXE Decking Oil or Arsinol Transparent is used. If the wood is very weathered or faded and need refreshing the FAXE Decking Oil or Arsinol Transparent in a similar colour is recommended.

**Storage:** Store above 5° C.**Shelf-life:** 12 Months in an unopened container**Cleaning:** The tools should be cleaned with water.**Note:** FAXE Decking Cleaner Conc. do not damage the adjacent vegetation.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**Esbjerg Farve- & Lakfabrik A/S****Energivej 13****DK- 6700 Esbjerg****Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk****www.esbjergpaints.dk**