

TECHNICAL DATA SHEET

en

Name of product:

FAXE Special Lye 0296

Type of product: Lye based on Sodium hydroxide.

Application: FAXE Special Lye is used on untreated oak, where a special surface is wanted. For oak, where a smoked or coloured tone is wanted or on softwood where the nature look is wanted.

Properties: FAXE Special Lye stops untreated pine, spruce and pitch pine from yellowing. Depending upon the type of wood, the heartwood will be accentuated, structure and grain will remain. Gives a smoked effect e.g. on oak.

Solids: 3 weight % 3 vol. %

Pre-treatment: The wood has to be sanded, clean and dry.

Application:

Method:

Industrial roller coater

Recommended viscosity:

No thinning required

Thinner:

Drying:

	Drying time	Film thickness - dry
Dry to use	5 hours 20 °C	.

System Specification:

Application:

1x FAXE Special Lye
1x Sanding

After Care:

1x FAXE Micro Oil or 1x FAXE Oxi. Industryoil

Coverage: Theoretical: 10 m²/ltr.

Storage: Frostfree, cool, and closed.

Shelf-life: 12 Months in an unopened container

Cleaning: The tools should be cleaned with water.

Available colors: FAXE Special Lye is not pigmented. In order to apply colour at the same time, add up to 10% FAXE Combicolor.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk