

TECHNICAL DATA SHEET

en

Name of product:

FAXE Decking Oil 0268

Type of product: Decking Oil containing vegetable oils, lightfast pigments and active ingredients.
Application: Treatment and renovation of cleaned wooden terraces and wooden garden furniture.
Properties: Protects from the elements and gives the wood a water-repellant surface. It also retains the woods natural appearance and color. Contains UV-absorber which protects the wood effectively from degeneration by sunlight.

Solids: 41 weight % 38 vol. %

Pre-treatment: Clean the wood with FAXE Decking Cleaner to remove all dirt and coverings.

Application:

Method:	Recommended viscosity:	Thinner:
Paint Brush	No thinning required	-

The product needs to be stirred well before and while it is used. If several buckets are going to be used, mix them together first.

Wipe off any excess oil after 15 minutes. Highly absorbent wood has to be treated several times.

Drying:

	Drying time	Film thickness - dry
Fully cured	36 hours 20 °C	-

Coverage: Theoretical: 10 m²/ltr.

Shelf-life: 12 Months in an unopened container

Cleaning: Tools clean with white spirit.

VOC explanation: Product marking: 2004/42/IIA(X)(YY)ZZZ EU directive number: 2004/42/
Directive annex number: IIA
Product subcategory: (X)
VOC content limit value g/l 2010: (YY)
Maximum VOC Content in this product when ready for use, g/l: ZZZ
Please see the can label for information regarding VOC content.

Note: The oil treatment should take place in dry weather and not in strong sunlight. Temperatures between 15 and 25°C. Contains drying oil. Oiled rags etc. may spontaneously combust. Waste, used cloths, etc, should be stored in fire-safe rubbish containers and destroyed.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk