

## TECHNICAL DATA SHEET

en

Name of product:

### Arsinol® Wood Care Oil 0173

<b>Type of product:</b>	Woodcare oil based on linseed oil and lightfast pigments. Contains active ingredients too.
<b>Application:</b>	Maintenance of hardwood, e.g. garden furniture, patios, facades, etc. This product has been developed for exterior use.
<b>Properties:</b>	Protects from the elements and gives the wood a water-repellant surface. It also retains the woods natural appearance and color.
<b>Solids:</b>	39 weight %      36 vol. %
<b>Pre-treatment:</b>	Clean the wood with FAXE Decking Cleaner 0580 99300 to remove all dirt and coverings.

#### Application:

<b>Method:</b>	<b>Recommended viscosity:</b>	<b>Thinner:</b>
Paint Brush	No thinning required	
Lint-free rags	No thinning required	

Take extra care when applying oil to the end surfaces as they are more absorbent than other surfaces. Wipe off any excess oil after 5 - 15 minutes. Repeat the treatment after 14 days.

#### Drying:

	<b>Drying time</b>	<b>Film thickness - dry</b>
Dry to touch	2 hours 20 °C	-
Waterproof after	8 hours 20 °C	-

**Coverage:** Theoretical: 14 m<sup>2</sup>/litr.

**Storage:** Store cool and dry

**Shelf-life:** 12 Months in an unopened container

**Available colors:** Please see our color card for information on the color range.

**VOC explanation:** Product marking: 2004/42/IIA(X)(YY)ZZZ

EU directive number: 2004/42/  
Directive annex number: IIA  
Product subcategory: (X)  
VOC content limit value g/l 2010: (YY)  
Maximum VOC Content in this product when ready for use, g/l: ZZZ

Please see the can label for information regarding VOC content.

**Note:** The oil treatment should take place in dry weather and not in strong sunlight. Temperatures between 10 and 25°C.

#### MAINTENANCE:

When the wood becomes weather-worn and is no longer water repellent, treat it again with Wood Care Oil.

Contains drying oil. Used rags may spontaneously ignite. Used rags should be stored in a fire-proof container or an airtight bag and discarded .

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**Esbjerg Farve- & Lakfabrik A/S**

**Energivej 13**

**DK- 6700 Esbjerg**

**Ph. +45 75 12 86 00    FAX +45 75 45 33 68    e-mail: [info@esbjergpaints.dk](mailto:info@esbjergpaints.dk)**

**[www.esbjergpaints.dk](http://www.esbjergpaints.dk)**