

**TECHNICAL DATA SHEET****en****Name of product:****FAXE Universal Lye THIX 0251****Type of product:** White lye based on vegetable oils, naturel wax, pigments and sodium hydroxide.**Application:** FAXE Universal Lye THIX, is a lye, which slows down the yellowing process of wood in a chemical way.**Properties:** Lye slows down the yellowing process - can be applied to roller and spray equipment.**Solids:** 8 weight % 8 vol. %**Pre-treatment:** The wood has to be sanded, clean and dry.**Application:****Method:**

Industrial roller coater

Spraying

**Recommended viscosity:**

No thinning required

No thinning required

**Thinner:**

-

-

FAXE Universal Lye THIX is made thixotropic so that it can be applied to the roller and spray equipment in the industry.

**Drying:**

	<b>Drying time</b>	<b>Film thickness - dry</b>
Dry to touch	5 hours 20 °C	20 - 25 gram / m <sup>2</sup>
Forced dry	5 minutes 40 °C	20 - 25 gram / m <sup>2</sup>

**System Specification:**

1x FAXE Universal Lye THIX

The product has to be stirred before and during use.

After Care:

Subsequently, the surface can be treated with oil, hardwax, Invisioil and the like, depending on the surface and the effect you want.

**Coverage:** Theoretical: 10 m<sup>2</sup>/ltr.**Storage:** Frostfree**Shelf-life:** 12 Months in an unopened container**Cleaning:** The tools should be cleaned with water.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**Esbjerg Farve- & Lakfabrik A/S****Energivej 13****DK- 6700 Esbjerg****Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk****www.esbjergpaints.dk**