

**TECHNICAL DATA SHEET****en**

Name of product:

**FAXE Maintenancepaste 0271****Type of product:** Maintenancepaste based on refined oils.**Application:** FAXE Maintenancepaste is used for care of oiled or oil/wax-treated wooden surfaces.**Properties:** Gives the wood a water and dirt repellent surface. It also retains its natural appearance and color.**Pre-treatment:** Clean the wood with Faxe Intensive Cleaner.**Application:****Method:**

Polishing pad

**Recommended viscosity:**

No thinning required

**Thinner:****Drying:**

	<b>Drying time</b>	<b>Film thickness - dry</b>
Dry to use	1 day(s) 20 °C	-
Dry through	2 day(s) 20 °C	-

**System Specification:**

1. Apply Maintenancepaste directly from the packaging with a pad.
2. Polish off the excess Maintenancepaste with an oil-absorbent cloth or felt-pad.

**Coverage:** Theoretical: 150 m<sup>2</sup>/ltr.**Storage:** Frostfree, cool, and closed.**Shelf-life:** 24 Months in an unopened container**Cleaning:** The tools should be cleaned with white spirit.**Note:** Avoid moisture and wash with water the first 2 days after the treatment.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**Esbjerg Farve- & Lakfabrik A/S****Energivej 13****DK- 6700 Esbjerg****Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk****www.esbjergpaints.dk**