

TECHNICAL DATA SHEET**en****Name of product:****FAXE Hardwood Oil 0279**

Type of product:	Hardwood Oil based on vegetable oil, active substances and when necessary light-resistant pigments.
Application:	FAXE Hardwood Oil is used as treatment and rehabilitation of e.g. garden furniture made of wood. FAXE Hardwood Oil is also suitable treatment of windows, doors and deckings.
Properties:	FAXE Hardwood Oil protects the wood against climatic influences. The pigments complements the colour of the tree and prevents the wood from a premature aging. Structure and drawing preserved by treatment with FAXE Hardwood Oil while providing an effective UV protection.
Pre-treatment:	Wooden furniture, deckings and very dirty windows and doors are cleaned with FAXE Wood Cleaner Outdoor and must then dry. At heavy dirt and weathering, we recommend a deep cleaning with FAXE Outdoor Cleaner 1 and 2. Be aware that new fresh hardwood (teak, mahogany, meranti, nyatoh and other exotic wood types) contains their own natural oils, one should clean the surface with FAXE Wood Cleaner Outdoor before treatment with oil.

Application:

Method:	Recommended viscosity:	Thinner:
Brush	No thinning required	-
Oil absorbing cloths	No thinning required	-
hand scrub	No thinning required	-

Drying:

	Drying time	Film thickness - dry
Dry to touch	24 hours 20 °C	-

System Specification:

Application:

* Stir the product thoroughly before and during use. If several containers containing identical product are to be used, they should be mixed together first in order to ensure a uniform result.

* The oil is coated evenly and let it stay on for 15 minutes. By highly absorbent wood repeat this if necessary several times. The oil is rubbed into the wood grain by hand scrubs.

* Possibly excess oil is wiped off.

Coverage:	Theoretical: 10 m ² /ltr.
Storage:	Frostfree, cool, and closed.
Shelf-life:	24 Months in an unopened container
Working temperature	The work must not be carried out in direct sunlight or heat, but in dry weather. Working temperature min. 15°C.
Cleaning:	Tools clean with white spirit 79120.
Note:	The surface is, depending on climate, hardened and solid after approx. 1-2 days. During curing protect the wood against water.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk