

## TECHNICAL DATA SHEET

en

Name of product:

### Efaspray Zincspray 0790 - 69045

**Type of product:** Zincous, anti-corrosive paint based on epoxy ester. Uses dimethyl ether as a propellant.

**Application:** Anti-corrosive primer for temporary or permanent protection.

**Properties:** Excellent adhesive and water resistant qualities. Outstanding galvanic corrosion protection abilities.

**Solids:** 52 weight % 37 vol. %

**Pre-treatment:** Sand blasting in accordance with SA 2½ is necessary to ensure good adhesion to steel.

**Application:**

**Method:**

**Recommended viscosity:**

**Thinner:**

-

**Drying:**

	<b>Drying time</b>	<b>Film thickness - dry</b>
Dust dry	5-10 minutes 20 °C	-
Dry to touch	30 minutes 20 °C	-
Dry to recoat	1 hour 20 °C	-

**Recommended coating thickness:** Wet film: 100 µm Dry film: 18 µm

**Coverage:** Theoretical: 10 m<sup>2</sup>/ltr.

**Storage:** Frostfree

**Shelf-life:** 12 Months in an unopened container

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**Esbjerg Farve- & Lakfabrik A/S**

**Energivej 13**

**DK- 6700 Esbjerg**

**Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk**

**www.esbjergpaints.dk**