

TECHNICAL DATA SHEET

en

Name of product:

Candle Lacquer W 0556

Type of product: Acrylic dispersion-based water-borne paint.

Application: Decorative coating for candles.

Properties: Fast-drying decorative paint.

Solids: 26 weight % 22 vol. %

Application:

Method:

Dipping

Except:

Product 0556-06086 25 sec. ± 2 F4.

Recommended viscosity:

14 - 20 sec. DIN-cup 4 mm

Thinner:

water

STIR THE PRODUCT THOROUGHLY BEFORE AND DURING USE.

Drying:

	Drying time	Film thickness - dry
Dry to touch	30 minutes 20 °C	-

Storage: Frostfree

Shelf-life: 12 Months in an unopened container

Cleaning: Tools clean with water.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk