

**TECHNICAL DATA SHEET****en**

Name of product:

**Faxe Oxi. Industry Oil****Type of product:** Wood Oil based on refined vegetable oils and evt. titanwhite.**Application:** Faxe Oxi Industry Oil is for application on untreated or lye treated solid wood and parquet flooring in living areas.**Properties:** It makes the wood dirt-resistant and hard-wearing.**Solids:** 59 weight % 54 vol. %**Pre-treatment:** The wood has to be sanded, clean and dry.  
Dirt has to be removed with Faxe Intensive Cleaner.**Application:****Method:**

Industrial roller coater

**Recommended viscosity:**

No thinning required

**Thinner:**

-

**Drying:**

	<b>Drying time</b>	<b>Film thickness - dry</b>
Resilient to careful use	5 hours 20 °C	12-15 g / m <sup>2</sup>
Fully cured	7 day(s) 20 °C	12-15 g / m <sup>2</sup>

**Coverage:** Theoretical: 37 m<sup>2</sup>/ltr.**Storage:** Frostfree, cool, and closed.**Shelf-life:** 24 Months in an unopened container**Cleaning:** Tools clean with white spirit.**Note:** If several containers containing identical product are to be used, they should be mixed together first in order to ensure a uniform result. It is always recommended to make a small test area to check surface, adhesion and colour tone.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**Esbjerg Farve- & Lakfabrik A/S****Energivej 13****DK- 6700 Esbjerg****Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk****www.esbjergpaints.dk**