

TECHNICAL DATA SHEET

en

Name of product:

FAXE Intensive Cleaner 0291

Type of product: Cleaning agent based on nonionic surfactants.

Application: FAXE Intensive Cleaner is a basic cleaning agent for all types of wood and wood surfaces in living areas:
* Cleaning of lye- or soap-treated wood before FAXE oil-treatment.
* Cleaning of ceilings, walls, panels etc. before treatment with FAXE Panel Lye.
* Removal of dirt, grease and old soap before refreshing with FAXE soap, oil or bee wax.
* Removal of difficult stains.
* Cleaning wherever a thorough cleaning is required.

System Specification:

Application:

- Fill 2 buckets with 5 litres of warm water. Add 1-2 cupfuls of FAXE Intensive Cleaner to one of the buckets.
- Use the FAXE Intensive Cleaner dilution to scrub or mop the wood thoroughly. Loosen stubborn dirt, pick it up with the mop and rinse the mop in clear water.
- Then wring the mop out and mop the floor with the clean water.

Aftercare:

When cleaning has been completed, new surface protection must be applied.

Coverage: Theoretical: 100 m²/ltr.

Storage: Frostfree, cool, and closed.

Shelf-life: 60 Months in an unopened container

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk