

TECHNICAL DATA SHEET

en

Name of product:

FAXE WPC Sealer 0280 17113

Type of product: FAXE WPC Sealer is a waterbased careing agent for surfaces made of WPC. FAXE WPC Sealer contains caring wax.

Application: Can be used on terraces, decking, fences, garden furniture etc.

Properties: FAXES WPC Sealer contains wax that creates a protective layer on the surface, which does not allow water and dirt to penetrate the surface. The treatment prevents up-building of growth.

Application:

Method: Brush and roller	Recommended viscosity: No thinning required	Thinner: -
------------------------------------	---	----------------------

Drying:

	Drying time	Film thickness - dry
Dry to touch	1 hour 20 °C	.

System Specification:

Work instructions:

1. Clean the surface with FAXE WPC Cleaner 0580 17119.
2. Shake FAXE WPC Sealer before use. Apply an even and thin layer on the surface with a brush. After approx. 1 hour drying apply a second layer of FAXE WPC Sealer.
3. If longer durability is wanted, we recommend application of 3-4 layers of FAXE WPC Sealer.

Coverage: Theoretical: 40 m²/ltr.

Storage: Frostfree, cool, and closed.

Shelf-life: 12 Months in an unopened container

Cleaning: The tools should be cleaned with water.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk