

## TECHNICAL DATA SHEET

en

Name of product:

### Arsinol™ Opaque 0171

<b>Type of product:</b>	Opaque, tixotrop wood preservative based on linseed oil. Contains non-fading color pigments with high hiding power.
<b>Application:</b>	Wood preservative for maintaining wood which has previously been treated with Arsinol™. This product has been developed for exterior use.
<b>Properties:</b>	Excellent hiding power that make color changes easier, even from dark to light colors. Arsinol™ Opaque has a gel-like consistency, but should not be stirred or diluted. If there is a little oil at the top of the bucket, the product can be assembled again by stirring it up. After a while the gelatinous consistency is maintained.
<b>Solids:</b>	67 weight %      50 vol. %
<b>Pre-treatment:</b>	Clean the wood for dirt and loose paint with a stiff brush. The wood must be completely dry (max. 15 % humidity) before painting. Coverings can be removed using FAXE Terrace Cleaner 0580 99300.

#### Application:

**Method:**

Paint Brush

**Recommended viscosity:**

No thinning required

**Thinner:**

The temperature must be between 5 and 25 °C and the relative humidity below 80% during both applying and drying.

Keep surface coatings wet until completed i.e coat one or two boards in their full length to avoid unsightly overlapping.

#### Drying:

	<b>Drying time</b>	<b>Film thickness - dry</b>
Dry to touch	8 hours 20 °C	.
Dry to recoat	24 hours 20 °C	.

#### System Specification:

1x Arsinol™ Transparent 0170  
1x Arsinol™ Opaque 0171

<b>Coverage:</b>	Theoretical: 10 m <sup>2</sup> /ltr.
<b>Storage:</b>	Dry and frost free.
<b>Shelf-life:</b>	24 Months in an unopened container
<b>Cleaning:</b>	Tools clean with white spirit 79120.
<b>Available colors:</b>	Please see our color card for information on the color range.
<b>VOC explanation:</b>	Product marking: 2004/42/IIA(X)(YY)ZZZ  EU directive number: 2004/42/ Directive annex number: IIA Product subcategory: (X) VOC content limit value g/l 2010: (YY) Maximum VOC Content in this product when ready for use, g/l: ZZZ  Please see the can label for information regarding VOC content.

**Note:** Avoid applying in direct sunlight. Contains drying oil. Used rags may spontaneously ignite. Used rags should be stored in a fire-proof container or an airtight bag and discarded .

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**Esbjerg Farve- & Lakfabrik A/S**  
**Energivej 13**  
**DK- 6700 Esbjerg**

**Ph. +45 75 12 86 00    FAX +45 75 45 33 68    e-mail: [info@esbjergpaints.dk](mailto:info@esbjergpaints.dk)**

**[www.esbjergpaints.dk](http://www.esbjergpaints.dk)**