

## TECHNICAL DATA SHEET

en

Name of product:

### Arsinol™ EXTRA 0175

**Type of product:** High solid content wood preservative.

**Application:** Wood preservative for maintaining wood which has previously been treated with Arsinol™. This product has been developed for exterior use.

**Properties:** Good adhesion, coverage and penetration of wood. Excellent hiding power that make color changes easier, even from dark to light colors.

Arsinol™ EXTRA is sunflower seed oil based and contains lightfast pigments and active ingredients. Since sunflower seed oil is light in color and does not turn yellow to the same degree as other vegetable oils, light colors stay nicely light for a longer time.

**Solids:** 85 weight % 75 vol. %

**Pre-treatment:** Clean the wood for dirt and loose paint with a stiff brush. The wood must be completely dry (max. 15 % humidity) before painting. Coverings can be removed using FAXE Terrace Cleaner 0580 99300.

**Application:**

|                |                               |                 |
|----------------|-------------------------------|-----------------|
| <b>Method:</b> | <b>Recommended viscosity:</b> | <b>Thinner:</b> |
| Paint Brush    | No thinning required          | -               |

The temperature must be between 5 and 25 °C and the relative humidity below 80% during both applying and drying.

Keep surface coatings wet until completed, i.e. coat one or two boards in their full length to avoid unsightly overlapping.

Arsinol™ EXTRA has a viscous consistency, but you do not need to dilute it. If you want the product to be a little thinner, you can add ca. 5% white spirit to Arsinol™ EXTRA.

**Drying:**

|               | <b>Drying time</b> | <b>Film thickness - dry</b> |
|---------------|--------------------|-----------------------------|
| Dry to touch  | 8 hours 20 °C      | -                           |
| Dry to recoat | 24 hours 20 °C     | -                           |

**System Specification:**

1x Arsinol™ Transparent 0170  
1x Arsinol™ Extra 0175

NB! If the wood is very dry, we recommend to apply 2x Arsinol™ Transparent 0170.

**Recommended coating thickness:** Wet film: 100 µm Dry film: 75 µm

**Coverage:** Theoretical: 10 m²/ltr.

**Storage:** Dry and frost free.

**Shelf-life:** 24 Months in an unopened container

**Cleaning:** Tools clean with white spirit 79120.

**Available colors:** Please see our color card for information on the color range.

---

**VOC explanation:** Product marking: 2004/42/IIA(X)(YY)ZZZ

EU directive number: 2004/42/  
Directive annex number: IIA  
Product subcategory: (X)  
VOC content limit value g/l 2010: (YY)  
Maximum VOC Content in this product when ready for use, g/l: ZZZ

Please see the can label for information regarding VOC content.

---

**Note:** Compared to Arsinol series 0171, Arsinol EXTRA series 0175 has a higher solids content and has an approximately 50% greater yield.  
Avoid applying in direct sunlight.  
Contains drying oil. Used rags may spontaneously ignite. Used rags should be stored in a fire-proof container or an airtight bag and discarded .

---

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

## **Esbjerg Farve- & Lakfabrik A/S**

**Energivej 13**

**DK- 6700 Esbjerg**

**Ph. +45 75 12 86 00    FAX +45 75 45 33 68    e-mail: [info@esbjergpaints.dk](mailto:info@esbjergpaints.dk)**

**[www.esbjergpaints.dk](http://www.esbjergpaints.dk)**